

WEST**End of Result Set**

Generate Collection

Print

L1: Entry 1 of 1

File: DWPI

Dec 4, 2001

DERWENT-ACC-NO: 2001-205246

DERWENT-WEEK: 200203

COPYRIGHT 2002 DERWENT INFORMATION LTD

TITLE: Thermal transfer material for printer, consists of thermal conversion layer and image forming layer which has specific smoothness and average surface roughness

INVENTOR: TAKAHASHI, Y

PATENT-ASSIGNEE:

ASSIGNEE

CODE

FUJI PHOTO FILM CO LTD

FUJF

PRIORITY-DATA: 1999JP-0167406 (June 14, 1999)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
US 6326121 B1	December 4, 2001		000	G03F007/34
JP 2000355177 A	December 26, 2000		014	B41M005/40

APPLICATION-DATA:

PUB-NO	APPL-DATE	APPL-NO	DESCRIPTOR
US 6326121B1	June 13, 2000	2000US-0592811	
JP2000355177A	June 14, 1999	1999JP-0167406	

INT-CL (IPC): B41 J 2/435; B41 M 5/26; B41 M 5/40; G03 B 27/60; G03 F 7/09; G03 F 7/34

ABSTRACTED-PUB-NO: JP2000355177A

BASIC-ABSTRACT:

NOVELTY - Light and heat conversion layer and an image forming layer formed on the support structure, are laminated. The smoothness of the image forming layer surface is 2 mmHgs or less and its central line average surface roughness Ra' is 0.03-0.2 mu m. The liquid applied for lamination has pigment particles in which particles size of 3% of particles in total weight is 1 mu m or more.

DETAILED DESCRIPTION - An INDEPENDENT CLAIM is also included for laser thermal transfer recording method which involves irradiating multi-mode semiconductor laser on the thermal conversion layer whose material is adhered to image forming layer material by vacuum pressure reduction method, to form the image in the image forming layer during which the lamination and thermal transfer layer are peeled off.

USE - For printer, recorder, facsimile connected to computer. Also for medical treatment.

ADVANTAGE - Gap between thermal transfer image receiver material is not generated, by performing uniform adhesion, thereby image is uniformly transferred from the layer. High resolution image is formed at high speed by using multi-mode semiconductor laser.

ABSTRACTED-PUB-NO:

US 6326121B

EQUIVALENT-ABSTRACTS:

NOVELTY - Light and heat conversion layer and an image forming layer formed on the support structure, are laminated. The smoothness of the image forming layer surface is 2 mmHgs or less and its central line average surface roughness Ra' is 0.03-0.2 μ m. The liquid applied for lamination has pigment particles in which particles size of 3% of particles in total weight is 1 μ m or more.

DETAILED DESCRIPTION - An INDEPENDENT CLAIM is also included for laser thermal transfer recording method which involves irradiating multi-mode semiconductor laser on the thermal conversion layer whose material is adhered to image forming layer material by vacuum pressure reduction method, to form the image in the image forming layer during which the lamination and thermal transfer layer are peeled off.

USE - For printer, recorder, facsimile connected to computer. Also for medical treatment.

ADVANTAGE - Gap between thermal transfer image receiver material is not generated, by performing uniform adhesion, thereby image is uniformly transferred from the layer. High resolution image is formed at high speed by using multi-mode semiconductor laser.

CHOSEN-DRAWING: Dwg.0/0

TITLE-TERMS: THERMAL TRANSFER MATERIAL PRINT CONSIST THERMAL CONVERT LAYER IMAGE FORMING LAYER SPECIFIC SMOOTH AVERAGE SURFACE ROUGH

DERWENT-CLASS: G05 P75 P82 P84 T04

CPI-CODES: G05-F01;

EPI-CODES: T04-G03B;

SECONDARY-ACC-NO:

CPI Secondary Accession Numbers: C2001-061354

Non-CPI Secondary Accession Numbers: N2001-146698